

Space Heater Specifications

Unit Name	SHEN TURBO™ 250 (Outside Canada)	SHEN TURBO™ (Canada)
Heating area per unit	2750-4400 ft ² (255.5-408.8 m ²)	2500-4000 ft ² (232.3-371.6 m ²)
Capacity (maximum per hour)		
Direct Spark or Hot Surface Ignition	250,000 BTU (63,000 Kcal) LP or Nat. Gas	225,000 BTU (56,700 Kcal) - LP 200,000 BTU (50,400 Kcal) - Nat. Gas
Gas Consumption (maximum) - LP		
Direct Spark or Hot Surface Ignition	2.73 gph (10.33 l/h)	2.46 gph (9.31 l/h)
Gas Consumption (maximum) - Natural Gas		
Direct Spark or Hot Surface Ignition	235.85 cfm (6.68 m ³ /h)	213.8 cfm (6.05 m ³ /h)
Gas Pressure Requirements (measured at inlet)		
LP	11" WC (27.5 Mbar)	11" WC (27.5 Mbar)
Natural Gas	7" WC (17.5 Mbar)	7" WC (17.5 Mbar)
Heater Size, Weight & Assembly Information		
Weight per Complete Unit	125 lbs. (56.7 kg)	125 lbs. (56.7 kg)
Height x Length x Width	30 x 24.5 x 19 inches (76.2 x 62.2 x 48.3 cm)	30 x 24.5 x 19 inches (76.2 x 62.2 x 48.3 cm)
Minimum Clearance to Combustibles		
Above, below and beside unit	20 in. (50.8 cm)	20 in. (50.8 cm)
Exhaust outlet	120 in. (304.8 cm)	120 in. (304.8 cm)
Electrical Requirements: 120 VAC (220/240 VAC 50 or 60 Hz)		

The policy of Shenandoah is one of continuous product improvement. We reserve the right to alter specifications without prior notice. Heating products should be installed only in accordance with local laws, codes and regulations. These products are not for residential use. Gas pipe layout assistance available to customers through authorized distributors.

CSA (Canadian Standards Association) approved models are available. All models meet stringent standards for low carbon monoxide.

www.shenmfg.com



Shenandoah® 800-704-7356

Manufactured by:



Agile Mfg., Inc. • A Subsidiary of CTB, Inc.
 720 Industrial Park Road • Anderson, MO 64831
 Phone 800-704-7356 or 417-845-6065 • Fax 417-845-6069
 E-mail: sales@agilemfg.com

AG-3018/201204