

Update : September 2009

STORAGEline™

		VOLUME		FILL HEIGHT
MODEL	HOPPER	m³	tons(*)	m(**)
Galvanized Day Bins				
Diameter 1,80 m				
6' Low	60°	1.7	1.1	2.93
6' High	60°	2.5	1.6	3.13
Diameter 2,10 m				
7' Low	60°	3.7	2.4	3.24
Galvanized Feed Storage Bins				
Diameter 1,80 m				
601	60°	3,9	2,5	3,38
602	60°	6	3,9	4,19
603	60°	8,1	5,3	5,01
604	60°	10,2	6,6	5,82
Diameter 2,10 m				
702	60°	8,7	5,7	4,56
703	60°	11,6	7,5	5,37
704	60°	14,5	9,4	6,18
705	60°	17,4	11,1	7,00
706	60°	20,3	13,2	7,81
Diameter 2,75 m				
902	60°	15,8	10,3	5,26
903	60°	20,6	13,4	6,07
904	60°	25	16,5	6,88
905	60°	30,2	19,6	7,70
906	60°	35	22,8	8,51
907	60°	39,8	25,9	9,32
Diameter 3,15 m				
1052	60°	23,4	15,2	5,79
1053	60°	30	19,5	6,60
1054	60°	36,6	23,8	7,42
1055	60°	43,2	28,1	8,23
1056	60°	49,8	32,4	9,04

Installation time : 3 skilled people : 1 bin per day.

(*) Capacity in tons is based on a specific weight of 0,65 kg/dm³ !

(**)601-604 Bins with safety cage on the ladder : plus 32 cm !

(**)702-706 Bins with safety cage on the ladder : plus 23 cm !

(**)902-907 Bins with safety cage on the ladder : plus 1 cm !

(**)1052-1056 Bins with safety cage on the ladder : no extra height !

Day Bins are not available with ladder, roof ladder,
mechanic and pneumatic fill system.